

1

2

3

$$\begin{matrix} \text{In} & \text{S} & 4' \\ a & 1 & 5 \end{matrix}$$

8

10
11
12
13
14
15
16
17
18

19
20
21
22
23
24
25
26
27

1 the magnetically conductive tube extends. Each pole of at least one of the upper and lower
2 pole plates and the upper and lower magnetically conductive plates includes a side wall that
3 extends in a direction parallel to a longitudinal axis of the magnetically conductive tube. Since
4 there are at least one upper magnetically conductive plate and at least one lower magnetically
5 conductive plate that are respectively attached to the upper pole plate and the lower pole plate,
6 the side walls and the permanent ring magnet of the rotor have a larger induction area
7 therebetween. In addition, the upper magnetically conductive plate, the upper pole plate, the
8 lower magnetically conductive plate, and the lower pole plate are stacked one another to
9 increase the passage of magnetic force. Thus, the rotor outputs a larger rotating torque and
10 rotates in a stabler manner without floating.

Summary of the Invention

11 It is the primary object of the present invention to provide stator pole plate assemblies
12 having a lager area for magnetic conduction between magnetic pole plates and a magnetically
13 conductive tube, thereby improving the magnetic conductivity of the line of the magnetic
14 force.

15 A stator in accordance with the present invention comprises a bobbin with a winding
16 wound therearound and having a central hole. Pole plates are mounted to both sides of the
17 bobbin. Each pole plate includes a plurality of poles and a central tubular portion. The poles of
18 the pole plate attached to a side of the bobbin and the poles of the pole plate attached to the
19 other side of the bobbin are alternately disposed. A magnetically conductive tube is extended
20 through the central hole of the bobbin and the central tubular portions of the pole plates.

21 Other objects, specific advantages, and novel features of the invention will become
22 more apparent from the following detailed description and preferable embodiments when
23 taken in conjunction with the accompanying drawings.

Brief Description of the Drawings

24 Fig. 1 is an exploded perspective view of a conventional stator.
25
26

1 Fig. 2 is an exploded perspective view of a first embodiment of a stator in accordance
2 with the present invention.

3 Fig. 3 is a longitudinal sectional view of the positioning stator in Fig. 2.

4 Fig. 4 is an exploded perspective view of a second embodiment of the stator in
5 accordance with the present invention.

6 Fig. 5 is an exploded perspective view of a third embodiment of the stator in accordance
7 with the present invention.

8 Fig. 6 is a longitudinal sectional view of the stator in Fig. 5.

9 Fig. 7 is a longitudinal sectional view illustrating a fourth embodiment of the stator in
10 accordance with the present invention.

11 **Detailed Description of the Preferred Embodiments**

12 Preferred embodiments in accordance with the present invention will now be described
13 with reference to the accompanying drawings.

14 Referring to Figs. 2 and 3, a stator in accordance with the present invention generally
15 includes a bobbin 1, a magnetically conductive tube 2, and upper and lower pole plates 3.

16 The bobbin 1 may be of any conventional bobbin for all kinds of D.C. brushless
17 motors and heat-dissipating fans. The bobbin 1 includes a winding 11 wound therearound and
18 a central hole 12 through which the magnetically conductive tube 2 extends.

19 The magnetically conductive tube 2 is made from a magnetically conductive material,
20 such as metal. The magnetically conductive tube 2 is extended through the upper and lower
21 pole plates 3 and the central hole 12 of the bobbin 1. A flange 21 is formed on an end of the
22 magnetically conductive tube 2 to prevent disengagement of the upper and lower pole plates 3.

23 The upper and lower plates 3 are made from a magnetically conductive material and
24 include an upper pole plate 3a and a lower pole plate 3b attached to upper and lower ends of
25 the bobbin 1, respectively. The upper pole plate 3a includes a central tubular portion 32 and a
26 plurality of poles 31. Similarly, the lower pole plate 3b includes a central tubular portion 32
27 and a plurality of poles 31. The poles 31 of the upper pole plate 3a and the poles 31 of the

lower pole plates 3b are alternately disposed. The central tubular portions 32 of the upper pole plate 3a and the lower pole plate 3b are aligned with the central hole 12 of the bobbin 1 to thereby allow the magnetically conductive tube 2 to extend therethrough. Thus, the pole plates 3 and the magnetically conductive tube 2 have a larger contact area therebetween and the passage of magnetic conduction between the pole plates 3 and the bobbin 2 is increased accordingly.

Referring to Fig. 3, in assembly, the upper pole plate 3a and the lower pole plate 3b are respectively attached to the upper side and the lower side of the bobbin 1 with the central tubular portions 32 of the upper and lower pole plates 3 (i.e., 3a and 3b) aligned with the central hole 12 of the bobbin 1. The magnetically conductive tube 2 is extended through the central tubular portions 32 of the upper and lower pole plates 3 and the central hole 12 of the bobbin 1. Thus, the pole plates 3 and the magnetically conductive tube 2 have a larger contact area therebetween and the passage of magnetic conduction between the pole plates 3 and the bobbin 2 is increased accordingly.

Fig. 4 illustrates a second embodiment of the stator in accordance with the present invention, wherein each pole 31 of the upper pole plate 3a and the lower pole plate 3b includes a longitudinal extension (not labeled) that extends in a direction parallel to a longitudinal direction of the magnetically conductive tube 2, thereby defining a magnetic pole face 33. It is noted that the magnetic pole faces 33 on the upper pole plate 3a and the magnetic pole faces 33 on the lower pole plate 3b are alternately disposed. In addition, the longitudinal extensions of the upper pole plate 3a extend downwardly and the longitudinal extensions of the lower pole plate extends upwardly. Thus, the stator includes magnetic pole faces 33 of larger area to thereby provide a better magnetic conductivity. In addition, when the magnetic pole faces 33 is in magnetic induction with the permanent ring magnet, the rotor outputs a higher rotating torque and rotates more stabler.

Figs. 5 and 6 illustrate a third embodiment of the stator in accordance with the present invention, wherein at least two upper pole plates 3 are attached to an upper side of the bobbin

1 and at least two lower pole plates 3 are attached to a lower side of the bobbin 1. The poles 31 of the upper pole plates 3 are aligned with each other and the poles 31 of the lower pole plates 3 are aligned with each other. In addition, the poles of the upper pole plates 3 and the poles 31 of the lower pole plates 3 are alternately disposed.

The uppermost one of the upper pole plate 3 includes a central tubular portion 32 projecting from an upper side thereof and extending away from the bobbin 1. The lowermost one of the upper pole plate 3 includes a central tubular portion 32 projecting from an underside thereof and extending into the central hole 12 of the bobbin 1. The remaining upper pole plates 3 each includes a central hole 32a that is aligned with the central tubular portions 32 of the uppermost one and the lowermost one of the pole plates 3.

The lowermost one of the lower pole plate 3 includes a central tubular portion 32 projecting from an underside side thereof and extending away from the bobbin 1. The uppermost one of the lower pole plate 3 includes a central tubular portion 32 projecting from an upper side thereof and extending into the central hole 12 of the bobbin 1. The remaining lower pole plates 3 each includes a central hole 32a that is aligned with the central tubular portions 32 of the uppermost one and the lowermost one of the lower pole plates 3.

The central tubular portion 32 of the uppermost one of the lower pole plates 3 and the central tubular portion 32 of the lowermost one of the upper pole plates 3 extend into the central hole 12 of the bobbin 1. The magnetically conductive tube 1 is extended through the central tubular portions 32 and the central hole 32a of the upper and lower pole plates 3 as well as the central hole 12 of the bobbin 1, best shown in Fig. 6. As a result, the magnetically conductive tube 2 and the central tubular portions 32 of the upper and lower pole plates 3 have a larger contact area therebetween and the passage of magnetic conduction between the pole plates 3 and the bobbin 2 is increased accordingly.

Fig. 7 illustrates a fourth embodiment of the stator in accordance with the present invention. In this embodiment, two upper pole plates 3 are attached to the upper side of the bobbin 1 and two lower pole plates 3 are attached to the lower side of the bobbin 1. Each pole

plate 3 includes a central tubular portion 32 and a plurality of poles 31. More specifically, the upper one of the upper pole plates 3 includes a central tubular portion 32 projecting from an upper side thereof and extending away from the bobbin 1. The lower one of the upper pole plates 3 includes a central tubular portion 32 projecting from an underside thereof and extending into the central hole 12 of the bobbin 1. The lower one of the lower pole plates 3 includes a central tubular portion 32 projecting from an underside thereof and extending away from the bobbin 1. The upper one of the lower pole plates 3 includes a central tubular portion 32 projecting from an upper side thereof and extending into the central hole 12 of the bobbin 1.

The poles 31 of the upper pole plates 3 are aligned with each other and the poles 31 of the lower pole plates 3 are aligned with each other. In addition, each pole 31 of the upper pole plate 3a and the lower pole plate 3b includes a longitudinal extension (not labeled) that extends in a direction parallel to a longitudinal direction of the magnetically conductive tube 2, thereby defining a magnetic pole face 33. Furthermore, the poles of the upper pole plates 3 and the poles 31 of the lower pole plates 3 are alternately disposed. The magnetically conductive tube 2 is extended through the central tubular portions 32 of the upper and lower pole plates 3 as well as the central hole 12 of the bobbin 1. As a result, the magnetically conductive tube 2 and the central tubular portions 32 of the upper and lower pole plates 3 have a larger contact area therebetween and the passage of magnetic conduction between the pole plates 3 and the bobbin 2 is increased accordingly. The stator includes magnetic pole faces 33 of a larger area to thereby provide a better magnetic conductivity. In addition, when the magnetic pole faces 33 is in magnetic induction with the permanent ring magnet, the rotor outputs a higher rotating torque and rotates more stably.

According to the above description, it is appreciated that each pole plate of the stator in accordance with the present invention includes a central tubular portion such that the magnetically conductive tube and the central tubular portions of the pole plates have a larger contact area when the magnetically conductive tube is extended through and thus connects the

1 pole plates. The area of magnetic conduction between the pole plates and the magnetically
2 conductive tube is increased, which increases the passage of magnetic conduction, thereby
3 improving the magnetic conductivity.

4 Although the invention has been explained in relation to its preferred embodiment as
5 mentioned above, it is to be understood that many other possible modifications and variations
6 can be made without departing from the scope of the invention. It is, therefore, contemplated
7 that the appended claims will cover such modifications and variations that fall within the true
8 scope of the invention.

0362043-051004